



STANDARD SPECIFICATIONS

Understructure:	5" I-Beam Longitudinals 4" Boxed Extrusion Crossmembers
Floor:	.250 Aluminum (5454)
Sides:	.180 (5454)
Side Post:	.180 Aluminum (5454) Formed Box Type
Top Rail:	Heavy Duty 8" Extrusion (6061)
Bottom Rub Rail:	Heavy Duty Extrusion (6061) Interlocking With Sides And Floor With Built-in Inside 5" Radius Plate
Tailgate:	.180 Aluminum (5454) Fully Welded, Air Operated Hardware with Grease Zerks.
Tarp Tie Bar:	Included
Bulkhead:	.180 Aluminum (5454) One Piece Wrap Around, With Shovel Bracket
Steps:	Inside And Out & Front Corner Step With Rubber Flaps
Construction:	Continuous Welded Construction
Frame:	26lb/ft
Frame Xmembers:	Hat Shaped Crossmembers
King Pin Plate:	3/8" High Carbon Plate
Suspension:	Page TSP Straddle Mount Single Point
Axles:	25,000 lbs. Capacity
Hub/Drum:	10 Stud Hub Pilot Mount
Wheels:	Steel Disc
Brakes:	16 1/2"x7" Non Asbestos With Auto Slack Adjusters
Tires:	14 Ply Tubeless Radials
Landing Gear:	2 Speed With Sand Pads, 160,000 lbs. Static Vertical Load
Tire Carrier:	Included
Electrical:	Flush Rubber Mounted, Weather/Shock Resistant LED Lights
Hoist:	Front Mount Telescopic

AT OPTIONAL EQUIPMENT

Additional Heights, Lengths & Widths	Extended Frame
Special Crossmember Spacing	Tailgate Seal
Heavier Gauge Deck & Sides	Wing Latches
Horizontal Side Braces	Stoker/Asphalt Door
Sloping Tailgate	Overlay/Wear Plate
Side Swing Tailgate	Popular Suspensions
2 Way Gate (Std. & Side Swing)	Third Axle Lifts
Sideboards, Aluminum Or Wood	Special Tires
Inverted Angle On Top Rail	Spreader Apron
Tarping Systems	Push Bumper
Aluminum Disc Wheels	High Lift Gate



Due To our Company's Continued Product Improvement Program, Specifications Are Subject To Change Without Notice.

R/S-Godwin Truck Body Co., LLC.
5168 South U.S. Highway 23
Ivel Kentucky 41642
1-800-826-7413 606-874-2151