

HYBRID

Series



Shown with options

STANDARD SPECIFICATIONS

Various body lengths from 13' to 20' and side heights from 30" to 64". (49", 52", 61" and 64" for extruded sides)

Abrasion resisting 3/16" AR450 *steel* floor with 12" radius formed in place for strength.

Crossmemberless "western style" understructure.

Load supporting formed trapezoid longbeams with shock absorbing rubber cushion in formed steel track for quiet ride.

High tensile *steel* bulkhead with high tensile or AR450 *steel* hoist well for strength and durability.

Durable **Huck** bolt construction with barrier at bolted connections to prevent electrolysis.

Lightweight 3/16" *aluminum* sides with vertical side braces, 8" heavy duty extruded *aluminum* top rail and 3/16" *aluminum* lower rails.

Air operated 3/16" *aluminum* tailgate with galvanized *steel* upward acting top and bottom hardware.

1/4" formed *aluminum* full rear post.

Recessed FMVSS108 L.E.D. lighting.

Full width or offset bolt-on *aluminum* cab protector in 16" to 42" lengths.

Front mount telescopic hoists sized for body lengths



AVAILABLE OPTIONS

Straight or sloped tailgate in high lift or conventional design.

Asphalt taper on rear

Bolt on spreader apron

Coal door or chute in gate

Horizontal side brace or smooth side design

Inverted angle, wood or aluminum boards on top of sides

Steel or aluminum front mount or frame mount hydraulic tank

Multiple oval lights in back of rear post

Additional marker lights on sides

Mid rail turn signals

Electric tarping system

Other options available

Lightweight interlocking extruded *aluminum* sides with

Air high lift gate. (unavailable with extruded sides)

Due To our Company's Continued Product Improvement Program, Specifications Are Subject To Change Without Notice.



R/S-Godwin Truck Body Co., LLC.
5168 South U.S. Highway 23
Ivel Kentucky 41642
1-800-826-7413 606-874-2151

An affiliate of The Godwin Group.