AUSERIES ALUMINUM BODY





AU SERIES

Aluminum Body



Sturdy stacked understructure

AU OPTIONAL EQUIPMENT

Cabshield (various lengths)
Aluminum Boards
Wood Boards
Various Tarping Systems
Window in Bulkhead
Various Hoist Configurations
Stainless Steel Drop Pin top
Tailgate Hardware

Bolt On Spreader Apron Fold Down Sides Shovel Holder 1/4" Aluminum Floor Additional Lighting Various Tool Boxes Asphalt (stoker) Door Smooth Body Option

STANDARD SPECIFICATIONS	
Lengths:	Available in inside lengths from 8'6" through 11'6"
Inside Width:	86" side to side
Side Heights:	12" through 18"
Tailgate Heights:	18" through 24"
Understructure:	Stacked design utilizing 6" Aluminum Rubber Cushioned Longsills gusseted to 3" Aluminum Crossmembers. Full width rear bolster
Floor:	3/16" Aluminum (5454 H34), with 2" radius floor to side, (except for Drop Side)
Bulkhead:	3/16" Aluminum, (5454 H34)
Sides:	3/16" Aluminum (5454 H34) Front post, 2 intermediate side post, Full depth rear post with a formed top rail. 6" front and rear board extension pockets
Tailgate:	3/16" Aluminum (5454 H34), 3 Panel , Double Acting top tailgate hardware with long chains and two sets of banjo plates. Manual tailgate release
Lights:	FMVSS108 with oval stop/tail/turn lights recessed in rear post. All lighting is LED recessed, shock mounted, complete with factory wiring
11.1.4	

Due To our Company's Continued Product Improvement Program, Specifications Are Subject To Change Without Notice.

Hoists sized for body lengths



Steel lower tailgate latches and pins



Standard upper tailgate hardware



Hoist: